Business License Inspections



Orem City ordinances require that each "...place of business shall be inspected by the City for compliance with building, fire, and health codes prior to opening for business." We have determined that those businesses in a home where no customers will be going to the home and there are not any employees are not required to have this inspection. All others need to have building inspections and most need fire inspections too.

The building inspectors are available to inspect on weekdays between 7:30 AM and 5:00 PM. To schedule your building inspection, contact 801-229-7060 at least one working day in advance. A copy of the type of things that we look at is attached.

Electrical, plumbing, heating or framing and other non-cosmetic remodel work that is being done to your building require that a permit be issued and inspections scheduled and passed for that work. If you are remodeling or building a new structure, the construction needs to be complete and approved before you will be able to have the business license inspection.

Business Name:	Date:	Page 1 of 2

CITY OF OREM BUILDING SAFETY DEPARTMENT BUSINESS LICENSE INSPECTION

Business A		
CORREC		
	EXITS, STAIRWAYS AND AISLES	
(DOOR TO REMAIN UNLOCKED
(ces.
ì		
(·	et a one-hour fire rating.
(Aisle spacing must be: 24" where no public access is allowed, storage rooms, e similar obstructions are on one side only, and 44" where merchandise or other s	similar obstructions are on two sides.
(of the stairs, with ends terminating in a newel post or returned to wall.	ose of the steps, continuous from the top
(Exit lights not lit.	
	ELECTRICAL	
(
(it of 6-1/2'.
(
	Junction boxes need covers installed or blanks in empty knockouts.	
	Label all circuits in the electrical panelbox.	
(
	be plugged into a wall outlet, and cannot be banked in tandem. The appliance r Fused disconnect strips are available with long cords.	must be plugged into the power strip.
(
(
(All cords across pathways need approved cord covers.	
(Outlet "doubler" must be fused-type.	
(All breakers marked spare to be kept in the off position.	
	HEATING EQUIPMENT	
(
(
(B-vent clearance must be maintained.	
(Water heaters shall be anchored or strapped in the upper one-third and in the lo	ower one-third
(Keep all combustibles at least 3' away from furnace and/or water heater.	
(Gas meters and piping exposed to possible vehicle damage need protection (bol	llards).
(Flexible gas line to water heater and/or furnace needs to be checked/replaced.	
	<u>EXTINGUISHERS</u>	
(<u></u> y
(
	located so that the travel distance is not greater than 75 feet between extinguish	ers throughout the building, best placed
	by exit doors. They should be mounted on the wall 3 to 5 feet high at the top of placed on a shelf off the floor.	f the extinguisher, but they may also be
	PLUMBING	
7		red
(Bathroom facilities must meet handicapped requirements: () plumbing und	
×.	() lever handles, () grab bars, () signage.	zo. same must be protecteu,
(
(Hose bibbs require backflow prevention	
,		

Business Name	:Date;	Page 2 of 2
() () () () () ()	HOUSEKEEPING Keep outside containers at least 10' from the buildings. Keep all combustibles at least 10' away from buildings, building overhangs, and proposed All trash dumpsters need to be a minimum of 5' away from buildings with combustive Keep oily rags in a closed metal can. Keep caps and lids on all combustible and flammable cans and containers. Combustible and flammable liquids can only be stored in approved containers. (Recombustible of combustible materials is allowed in equipment rooms (Mechanical & Compressed gas cylinders need to be secured to prevent falling. (CO2, O2, Helium,	d plastic or metal)
() () () ()	FIRE SPRINKLERS 18" of clearance is required for storage below sprinkler heads. Main fire sprinkler riser needs to be visible and accessible. Fire sprinkler system needs to be electronically supervised for water flow and main over 20 sprinkler heads. Chain and lock the main fire sprinkler valve in the open position in buildings not re Outside Fire Department connection for the fire sprinkler system must not be obstruvegetation, etc.) And they need to have end caps in place. Spare fire sprinkler heads and wrench are required by the main fire sprinkler riser. Replace damaged fire sprinkler heads.	equired to be electrically supervised.
()	FIRE MARSHAL INSPECTION NEEDED	
()	ADDRESS Address numbers need to be visible from the street, a minimum 4 inch letters (or land the order of th	rger) with contrasting background.
	T	

MAKE CORRECTIONS WITHIN TWO WEEKS AND CALL 801-229-7060 FOR REINSPECTION.

A COPY OF THIS CHECKLIST MUST REMAIN ON SITE FOR REINSPECTION.